



Blaupunkt Monoblok BLP15P3V2MR32



ENJOY IT!

Air source inverter heat pump, monoblock					
		BLP15P3V2MR32			
Power Supply	V/Hz	380-420/50 3F			
Refrigerant	-	R32			
Max. Heating Capacity	kW	15,80			
C.O.P	-	4,62			
Heating Capacity Min./Max.	kW	7,27 / 15,80			
Heating Power Input Min./Max.	W	1259 / 3420			
C.O.P Min./Max.	-	4,62 / 5,78			
Max. Heating Capacity	kW	14,86			
C.O.P	-	2,88			
Heating Capacity Min./Max.	kW	6,84 / 14,86			
Heating power input Min./Max.	W	2050 / 5156			
C.O.P Min./Max.	-	2,88 / 3,34			
Max. Heating Capacity	kW	11,52			
C.O.P	-	3,38			
Heating Capacity Min./Max.	kW	5,30 / 11,52			
Heating power input Min./Max.	W	1467 / 3411			
C.O.P Min./Max.	-	3,38 / 3,61			
Max. Heating Capacity	kW	11,24			
C.O.P	-	2,17			
Heating Capacity Min./Max.	kW	5,17 / 11,24			
Heating power input Min./Max.	W	2223 / 5170			
C.O.P Min.	-	2,17/2,33			
Max Current	A	10,83			
Compressor	Type - Quantity/System	-	Twin Rotary Inverter		
Fan	Quantity	-	1		
	Airflow	m ³ /h	3500		
	Rated power	W	120		
Water Side Heat Exchanger	Type	-	Plate heat exchanger		
	Water Pressure Drop	kPa	21		
	Piping Connection	cal	G1"		
Allowable Water Flow	Min./Rated./Max.	L/S	0,47	0,75	1,26
Noise Level	db (A)	60			
Net Dimension (LxDxH)	mm	1110*475*960			
Packing Dimension (LxDxH)	mm	1200*540*1120			
Net Weight	kg	98			
Gross Weight	kg	126			

Performance tables

BLP15P3V2MR32		
Heating capacity (KW)		
7,23	7,49	7,49
8,22	8,23	8,44
9,44	9,04	9,46
11,52	11,44	11,24
12,54	12,31	12,26
12,80	12,56	12,51
14,22	13,95	13,90
15,80	15,17	14,86
16,59	15,93	16,62
17,42	16,72	17,43
30/35	40/45	50/55
COP kW/kW		
2,32	2,03	1,60
2,55	2,21	1,76
2,87	2,40	1,91
3,38	2,79	2,17
3,66	3,03	2,36
4,02	3,40	2,65
4,62	3,70	2,88
5,17	3,99	3,11
5,80	4,67	3,64
35	45	55

