



Blaupunkt Air Conditioners 2.5 kW

Blaupunkt AC2.5S1R32



Enjoy it.

Technical Specifications of AC2.5S1R32 Air Conditioner

Blaupunkt AC2.5S1R32			
Model	Indoor		BLP02.5PIACTIINR32
	Outdoor		BLP02.5PIACTISPR32,
Power supply	Ph-V-Hz		220-240V,1Ph,50Hz
Rated Cooling	Btu/h		9000(3500~11000)
Cooling Power input	W		628 (80~1100)
Cooling Current	A		2.73 (0.35~4.78)
EER	W/W		4,20
Rated Heating	Btu/h		10000(2800~11500)
Heating Power input	W		651 (70~990)
Heating Current	A		2.83 (0.32~4.32)
COP	W/W		4,50
Seasonal Cooling	Pdesignc	kW	2.6
	SEER	W/W	8.8
	Energy Efficiency Class		A+++
Heating(Average)	Pdesignh	kW	2.4
	SCOP	W/W	4.6
	Energy Efficiency Class		A++
	Tbiv	°C	-7
Heating(Warmer)	Pdesignh	kW	2.7
	SCOP	W/W	6.0
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Heating(Colder)	Pdesignh	kW	3.0
	SCOP	W/W	3.5
	Energy Efficiency Class		A
	Tbiv	°C	-10
Compressor	Type		ROTARY
Refrigerant	Type		R32
	GWP		675
	Charged quantity	Kg	0.62
Indoor air flow (Hi/Mi/Lo)	m3/h		510/360/300
Indoor noise level (Hi/Mi/Lo/Si)	dB(A)		37.0/31.0/22.0/19
Indoor sound power level	dB(A)		54
Outdoor air flow	m3/h		2150
Outdoor sound pressure level	dB(A)		54.0
Outdoor sound power level	dB(A)		58
Indoor unit	Dimension(W*D*H)	mm	802*200*295
	Packing (W*D*H)	mm	875*285*380
	Net/Gross weight	Kg	8.7/11.5
Outdoor unit	Dimension(W*D*H)	mm	765x303x555
	Packing (W*D*H)	mm	887x337x610
	Net/Gross weight	Kg	26.4/28.8
Design pressure	MPa		4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)
	Max. refrigerant pipe length	m	25
	Max. difference in level	m	10
Connection wiring			1.5x5//
Plug type			//no-plug
Thermostat type			(Remote Control)
Room temperature	Indoor(cooling/ heating)	°C	16~32/0~30
	Outdoor(cooling/heating)	°C	-15~50/-20~24
Qty/per 20' /40' /40'HQ			99/208/240

BLAUPUNKT

Blaupunkt Air Conditioners 3.5 kW

Blaupunkt AC3.5S1R32

R32
eco

A+++

A+++



Enjoy it.

Technical Specifications of the AC3.5S1R32 Air Conditioner.

Blaupunkt AC3.5S1R32			
Model	Indoor		BLP03.5P1AC1INR32
	Outdoor		BLP03.5P1AC1SPR32
Power supply	Ph-V-Hz		220-240V,1Ph,50Hz
Rated Cooling	Btu/h		12000(4700~14700)
Cooling Power input	W		1005 (130~1650)
Cooling Current	A		4.37 (0.6~7.2)
EER	W/W		3,50
Rated Heating	Btu/h		13000(3640~14950)
Heating Power input	W		977 (160~1560)
Heating Current	A		4.24 (0.7~6.78)
COP	W/W		3,90
Seasonal Cooling	Pdesignc	kW	3.5
	SEER	W/W	8.5
	Energy Efficiency Class		A+++
Heating(Average)	Pdesignh	kW	2.6
	SCOP	W/W	4.6
	Energy Efficiency Class		A++
	Tbiv	°C	-7
Heating(Warmer)	Pdesignh	kW	3.1
	SCOP	W/W	6.0
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Heating(Colder)	Pdesignh	kW	3.3
	SCOP	W/W	3.5
	Energy Efficiency Class		A
	Tbiv	°C	-10
Compressor	Type		ROTARY
Refrigerant	Type		R32
	GWP		675
	Charged quantity	Kg	0.62
Indoor air flow (Hi/Mi/Lo)	m3/h		520/370/310
Indoor noise level (Hi/Mi/Lo/Si)	dB(A)		39/33/22/21
Indoor sound power level	dB(A)		55
Outdoor air flow	m3/h		2200
Outdoor sound pressure level	dB(A)		54.5
Outdoor sound power level	dB(A)		61
Indoor unit	Dimension(W*D*H)	mm	802*200*295
	Packing (W*D*H)	mm	875*285*380
	Net/Gross weight	Kg	8.7/11.3
Outdoor unit	Dimension(W*D*H)	mm	765x303x555
	Packing (W*D*H)	mm	887x337x610
	Net/Gross weight	Kg	26.4/28.7
Design pressure	MPa		4.3/1.7
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)
	Max. refrigerant pipe length	m	25
	Max. difference in level	m	10
Connection wiring			1.5x5//
Plug type			//no-plug
Thermostat type			Remote Control
Room temperature	Indoor(cooling/ heating)	°C	16~32/0~30
	Outdoor(cooling/heating)	°C	-15~50/-20~24
Qty/per 20' /40' /40'HQ			99/208/240



Blaupunkt Air Conditioners 5 kW

Blaupunkt AC5.0S1R32



Enjoy it.

Technical Specifications of the AC5.0S1R32 Air Conditioner.

Blaupunkt AC5.0S1R32			
Model	Indoor		BLP05.0P1AC1INR32
	Outdoor		BLP05.0P1AC1SPR32
Power supply	Ph-V-Hz		220-240V,1Ph,50Hz
Rated Cooling	Btu/h		18000(6600~21400)
Cooling Power input	W		1550 (150~2250)
Cooling Current	A		6.7 (0.7~9.8)
EER	W/W		3,40
Rated Heating	Btu/h		19000(4400~23900)
Heating Power input	W		1630 (220~2350)
Heating Current	A		7.1 (0.95~10.2)
COP	W/W		3,42
Seasonal Cooling	Pdesignc	kW	5.3
	SEER	W/W	7,0
	Energy Efficiency Class		A++
Heating(Average)	Pdesignh	kW	4.2
	SCOP	W/W	4,0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
Heating(Warmer)	Pdesignh	kW	4.5
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Heating(Colder)	Pdesignh	kW	6.7
	SCOP	W/W	3.1
	Energy Efficiency Class		B
	Tbiv	°C	-10
Compressor	Type		ROTARY
Refrigerant	Type		R32
	GWP		675
	Charged quantity	Kg	1.1
	Indoor air flow (Hi/Mi/Lo)	m3/h	800/600/500
Indoor noise level (Hi/Mi/Lo/Si)	dB(A)	41/37/31/20	
Indoor sound power level	dB(A)	56	
Outdoor air flow	m3/h	2100	
Outdoor sound pressure level	dB(A)	57	
Outdoor sound power level	dB(A)	65	
Indoor unit	Dimension(W*D*H)	mm	971*228*321
	Packing (W*D*H)	mm	1045*305*405
	Net/Gross weight	Kg	11.2/14.6
Outdoor unit	Dimension(W*D*H)	mm	805x330x554
	Packing (W*D*H)	mm	915x370x615
	Net/Gross weight	Kg	33.5/36.1
Design pressure	MPa	4.3/1.7	
Refrigerant piping	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/12.7mm(1/2in)
	Max. refrigerant pipe length	m	30
	Max. difference in level	m	20
Connection wiring			1.5x5//
Plug type			//no-plug
Thermostat type			(Remote Control)
Room temperature	Indoor(cooling/ heating)	°C	16~32/0~30
	Outdoor(cooling/heating)	°C	-15~50/-20~24
Qty/per 20' /40' /40'HQ			86/174/204